

## **Motor Oil Longlife-III Synthetic 0W-30**

Fully Synthetic MID SAPS Passenger Car Motor Oil

**Motor Oil Longlife-III Synthetic 0W-30** is a high performance fuel saving MID SAPS long life oil based on 100% synthetic technology for use in gasoline- and diesel engines of passenger cars and light vans where a VAG norm VW 504.00/507.00 has been prescribed.

Product Code: 79370

## Remark: not suitable for R5- en V10 TDI engines and engines where VAG norm VW 506.01 is being advised.

**Motor Oil Longlife-III Synthetic 0W-30** is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Extended oil drain interval.
- Also suitable for engines equipped with other catalyst like TWC.

## Motor Oil Longlife-III Synthetic 0W-30 meets the following performance criteria:

ACEA C3 VW 504.00/507.00 Porsche C30 BMW LL-04

## **Typical Analysis**

| Properties            | Unit               | Method     | Typical Value |
|-----------------------|--------------------|------------|---------------|
|                       |                    |            |               |
| SAE Grade             |                    | SAE J300   | 0W-30         |
| Density @15°C         | kg/m³              | ASTM D4052 | 843.3         |
| Kin. Viscosity @40°C  | mm <sup>2</sup> /s | ASTM D7042 | 64.1          |
| Kin. Viscosity @100°C | mm <sup>2</sup> /s | ASTM D7042 | 12.3          |
| Viscosity Index       |                    | ASTM D2270 | 193           |
| Viscosity CCS @-35°C  | сР                 | ASTM D5293 | 5800          |
| Flash Point COC       | °C                 | ASTM D92   | 210           |
| Pour Point            | °C                 | ASTM D7346 | -53           |
| Total Base Number     | mgKOH/g            | ASTM D2896 | 8.2           |
| Sulphated Ash         | %Wt                | ASTM D874  | 0.7           |

Date Issued: 3-12-2024 Supersedes: 7-6-2024 Revision Nr.: 04