



Gear Oil MP 85W-140

Product Code: 76310

Automotive mineral Gear Oil MP 85W-140

Gear Oil MP 85W-140 is an universal high performance mineral MP gear oil for use in manual transmission en transaxles of passenger cars, vans, light- and heavy commercial vehicles, off-highway equipment, mining and agriculture where a SAE 85W-140 GL-5 is been required.

Gear Oil MP 85W-140 is formulated with high refined mineral base stocks in combination with a special MP-additive technology to achieve the following performance:

- Very good protection against wear.
- Very good performance against the forming of foam and corrosion.
- Good Oxidation- and thermal stability.

Gear Oil MP 85W-140 meets the following performance criteria:

API GL-5

MIL-L-2105D

Volvo STD 1273.1

ZF TE-ML 05A, 07A, 08, 12E, 16C, 16D, 21A

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	85W-140
Density @15°C	kg/m ³	ASTM D4052	908.8
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	390.1
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	27.7
Viscosity Index		ASTM D2270	97
Viscosity Brookfield @-12°C	cP	ASTM D5293	69000
Flash Point COC, min	°C	ASTM D92	>210
Pour Point	°C	ASTM D7346	-15

Date Issued: 19-12-2024	Supersedes: 04-03-2021	Revision Nr.: 03
-------------------------	------------------------	------------------