



Gear Oil MP 80W-90

Product Code: 76340

Automotive Multi Purpose Mineral Gear Oil

Gear Oil MP 80W-90 is an universal high performance mineral multi purpose gear oil for use in different applications, such as; manual transmission and transaxles of passenger cars, vans, light- and heavy commercial vehicles, off-highway equipment, mining and agriculture, where a SAE 80W-90 GL-5 oil is been required.

Gear Oil MP 80W-90 is formulated with high refined mineral base stocks in combination with a special additive technology to achieve the following performance:

- Very good protection against wear.
- Very good performance against the forming of foam and corrosion.
- Good Oxidation- and thermal stability.

Gear Oil MP 80W-90 meets the following performance criteria:

API GL-5 MIL-L-2105D Volvo STD 1273.1 MAN 342 M2
 ZF TE-ML 05A, 7A, 12E, 16B, 16C, 17B, 19B, 21A

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	80W-90
Density @15°C	kg/m ³	ASTM D4052	885.7
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	124.9
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	14.1
Viscosity Index		ASTM D2270	112
Viscosity Brookfield @-26°C	cP	ASTM D5293	60000
Flash Point COC, min	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36

Date Issued: 19-12-2024	Supersedes: 05-03-2021	Revision Nr.: 04
-------------------------	------------------------	------------------