

## Gear Oil LS 85W-140

"Limited Slip" Automotive Gear Oil

**Gear Oil LS 85W-140** is an extra high performance extreme pressure type automotive gear lubricant specially developed for use in modern high performance passenger cars, sports utility vehicles, vans and light duty trucks with limited slip differentials.

Product Code: 76430

**Gear Oil LS 85W-140** is based on high quality mineral virgin base oil in combination with a special additive package to ensure the following properties:

- Exceptional thermo-oxidative stability.
- Exceptional load bearing characteristics.
- Effective rust and corrosion protection.
- Excellent limited slip performance to reduce chatter and improves traction.
- Outstanding low temperature fluidity provides smoother shifting at low ambient temperatures.
- Exceptional shear stable.
- Good frictional properties provide improved fuel economy and smoother shift ability

**Gear Oil LS 85W-140** exceeds the following performance criteria:

API GL 5 MIL PRF 2105D BG 13895-2018 ZF TE-ML 07A

## **Typical Analysis**

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	85W-140
Density @15°C	kg/m³	ASTM D4052	903.5
Kin. Viscosity @40°C	mm²/s	ASTM D7042	343.5
Kin. Viscosity @100°C	mm²/s	ASTM D7042	25.8
Viscosity Index		ASTM D2270	98
Brookfield Viscosity @-12°C	сР	ASTM D2983	50000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-21