



Hydraulic Oil HLPD 68

Product Code: 76660

Mineral hydraulic fluid

Hydraulic Oil HLPD 68 is heavy duty detergent type ashless anti-wear hydraulic oil specially developed for machine-tool hydraulic systems, mobile hydraulic systems and clutch drives where minor water contamination can be expected.

Hydraulic Oil HLPD 68 is formulated with high quality mineral base oil in combination with a special additive package to ensure to following properties.

- Special detergent and dispersant properties ensure smooth functioning of hydraulic systems by minimizing formation of sticky residues and deposits.
- Excellent water emulsifying ability maintains proper functioning of hydraulic systems even in case of contamination of oil with small amounts of water .
- Superior anti-wear properties help reduce wear of mechanical components .
- High resistance to oxidation and thermal degradation controls the formation of sludge & varnish and improves oil life .
- Superior foam control and rapid air release properties ensure trouble-free operations.
- Effective corrosion inhibitors provide corrosion protection in arduous service conditions.
- Superior thermo- and oxidation stability.

Hydraulic Oil HLPD 68 exceeds the following performance criteria:

DIN 51524-2 HLPD DBL 6713 HLPD

Typical Analysis

Properties	Unit	Method	Typical Value
ISO VG Grade		ISO 3448	68
Density @15°C	kg/m ³	ASTM D4052	882.9
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	69.7
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	8.9
Viscosity Index		ASTM D2270	101
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-24

Date Issued: 3-1-2025	Supersedes: 19-12-2023	Revision Nr.: 1
-----------------------	------------------------	-----------------