



4-Stroke Motorcycle Oil Synthetic 20W-50

Product Code: 76790

Full Synthetic Oil for 4-stroke motorcycles.

4-Stroke Motorcycle Oil Synthetic 20W-50 is a high performance full synthetic engine oil specially designed for use in 4-stroke motorcycles with work under severe operation conditions and is can be used in gearbox and wet clutches.

4-Stroke Motorcycle Oil Synthetic 20W-50 is based on high quality full synthetics (PAO) base stocks in combination with a special selected additive package to obtain the following properties.

- Extreme good thermal- and oxidation stability.
- Excellent anti-wear, anticorrosion and antifoam properties.
- High friction properties to eliminate clutch slippage.
- Low temperature to ensure an easy cold start.

4-Stroke Motorcycle Oil Synthetic 20W-50 exceeds the following performance criteria:

API SN

JASO MA-2

Typical Analysis

Properties	Unit	Test Method	Typical Value
SAE Grade		SAE J300	20W-50
Density @15°C	kg/m ³	ASTM D4052	860.3
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	142.5
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	19.9
Viscosity Index		ASTM D2270	161
Viscosity -15°C	cP	ASTM D5293	4700
Flashpoint COC	°C	ASTM D92	>201
Pourpoint	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	8.4
Sulphated Ash	% Wt	ASTM D874	1.16

Date Issued: 6-1-2025

Supersedes: 13-4-2021

Revision Nr.: 03