



## 2-Stroke Motorcycle Oil Min

Product Code:76820

Mineral 2-stroke motorcycle oil

**2-Stroke Motorcycle Oil Min** is a high quality lubricant suitable for use in air cooled 2-stroke gasoline engines deployed in variety of applications.

**2-Stroke Motorcycle Oil Min** is based on a high quality virgin base oils in combination with a special selected additive package to obtain the following properties:

- Excellent lubricity protects against piston scuffing and premature wear of engine components
- Proven additive technology controls engine and exhaust system deposits
- Low ash formula prevents pre-ignition and spark plug fouling
- Easy miscibility with gasoline ensures stable homogeneous mixture even at low ambient temperatures.

**2-Stroke Motorcycle Oil Min** exceeds the following performance criteria:

API TC

JASO FB

### Typical Analysis

Properties	Unit	Method	Typical Value
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	879.8
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	71.1
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	9.4
Viscosity Index		ASTM D2270	111
Flash Point COC	°C	ASTM D92	160
Pour Point	°C	ASTM D7346	-30
Total Base Number	mgKOH/g	ASTM D2896	1.2
Sulphated Ash	%Wt	ASTM D874	0.25

Date Issued: 6-1-2025	Supersedes: 06-07-2023	Revision Nr.: 04
-----------------------	------------------------	------------------