



Chain Saw Oil 46

Product Code: 77030

Chain Saw Oil

Chain Saw Oil 46 is a high quality oil specially developed to lubricate the chain of chain saws.

Chain Saw Oil 46 is based on high quality virgin mineral base oil in combination with an unique additive package to ensure the following properties:

- Very good adhesive strength.
- Excellent lubricating properties, helps to prevent premature chain failure
- Extend working life.
- The specially selected additives also inhibit rust.
- Very low Pourpoint

Chain Saw Oil 46 is **NOT** suitable to lubricate the engine.

Typical Analysis

| Properties | Unit | Method | Typical Value |
|-----------------------|--------------------|------------|---------------|
| ISO VG Class | | | 46 |
| Density @15°C | kg/m ³ | ASTM D4052 | 874.7 |
| Kin. Viscosity @40°C | mm ² /s | ASTM D7042 | 48.7 |
| Kin. Viscosity @100°C | mm ² /s | ASTM D7042 | 7.3 |
| Viscosity Index | | ASTM D2270 | 110 |
| Flash Point COC | °C | ASTM D92 | >201 |
| Pour Point | °C | ASTM D7346 | -27 |

| | | |
|-----------------------|------------------------|------------------|
| Date Issued: 9-1-2025 | Supersedes: 21-04-2021 | Revision Nr.: 03 |
|-----------------------|------------------------|------------------|