

## **Industrial Gear Oil 100**

Mineral Industrial Gear Oil

**Industrial Gear Oil 100** is a high performance extreme pressure gear oils developed for lubrication of heavy duty industrial gears working under severe operating conditions.

**Industrial Gear Oil 100** is based on high quality mineral base oil in combination with an unique additive package to ensure the following properties:

- Excellent load carrying capability protects gears against scuffing and wear and offers long equipment life and reduced maintenance costs.
- High thermo-oxidative stability helps resist deposit formation, provides enhanced system cleanliness and enables longer service intervals.
- Provides effective rust and corrosion protection to all gearbox components.
- Excellent demulsibility property enables trouble-free operation in conditions encountering water/ moisture.

**Industrial Gear Oil 100** exceeds the following performance criteria:

DIN 51517-3 CLP David Brown S1.53.101 AIST 224 (US Steel 224) AGMA 9005-F16 AGMA 9005 E-02 ISO 12925-1 CKD JIS K 2219:2006 class 2

Product Code: 77060

## **Typical Analysis**

Properties	Unit	Method	Typical Value
ISO VG Grade		ISO 3448	100
Density @15°C	kg/m³	ASTM D4052	885.9
Kin. Viscosity @40°C	mm²/s	ASTM D7042	94.2
Kin. Viscosity @100°C	mm²/s	ASTM D7042	10.8
Viscosity Index		ASTM D2270	98
Flash Point COC,	°C	ASTM D92	>210
Pour Point	°C	ASTM D7346	-24
FZG Fail Load Stage		DIN 51354-2	>12
Total Acid Number	mgKOH/g	ASTM D664	0.5

Date Issued: 7-1-2025 Supersedes: 16-04-2021 Revision Nr.: 03