



## Compressor Oil 100

Mineral compressor oil

Product Code: 77610

**Compressor Oil 100** is a high performance ashless air compressor oil specially designed to meet the stringent requirements of major compressor manufacturers.

**Compressor Oil 100** is suited for reciprocating air-, rotary screw and vane compressors. Also used in circulating oil systems, plain and rolling element bearings, lightly loaded gear sets, etc.

**Compressor Oil 100** is based on high quality hydrotreated mineral base oil in combination with an unique additive package to ensure the following properties:

- Excellent thermo- and oxidative stability.
- Improved equipment reliability, availability and efficiency.
- Low ash and carbon forming tendency ensures improved valve performance.
- Reduced potential for fires and explosions in the discharge systems.
- Exceptional wear and rust.
- Superior demulsibility reduces oil carryover and corrosion, maintains lubrication efficiency.
- Reduces sludge formation and improves life of coalesces.

**Compressor Oil 100** exceeds the following performance criteria:

DIN 51506 VBL/VCL/VDL ISO/DP 6521 DAA/DAB/DAG/DAH DIN 51503-1 KAA/KE

### Typical Analysis

Properties	Unit	Method	Typical Value
ISO VG Grade		ISO 3348	100
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	865.0
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	99.5
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	12.2
Viscosity Index		ASTM D2270	114
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33

Date Issued: 8-1-2025	Supersedes: 19-04-2021	Revision Nr.: 03
-----------------------	------------------------	------------------