



ATF CVT Plus

Product Code: 78420

Automatic Transmission Fluid

ATF CVT Plus is a fully synthetic ultra-high performance CVT fluid formulated with selected base stocks and specially developed for use in the latest generation of Continuously Variable Transmission (CVT) – gearboxes which transfer traction via steel-made traction chain or push-belts.

ATF CVT Plus is formulated on high refined synthetic base stock in combination with an unique additive package to reach the following properties.

- Good thermo-and oxidation.
- Extended drain interval possible.
- Excellent antiwear, antirust and anticorrosion technology.
- High Viscosity index ensures adequate lubrication in both high operating & low starting temperatures.
- Better foam control leads to smooth & lasting shift feel and reduces fluid loss.
- Enhanced Low temperature fluidity assist in good cold start performance.
- Compatibility with all common seal materials

ATF CVT Plus exceeds the following performance criteria:

Audi/VW G 052 180	Ford Mercon C	Daihatsu Ammix CVTF-DC, CVTF-DFE
Audi/VW G 052 516	Ford M2C928-A	Ford WSS-M2C933-A
BMW EZL 799A	Honda HCF-2	Honda Genuine CVT Fluid
FCA CVTF+4	Hyundai/Kia SP CVT-1	Honda Multi Matic Fluid (HMMF)
GM DEX-CVT	MB 236.20	Mazda CVTF 3320 / JWS 3320
GM CVT	Nissan NS-1/NS-2/NS-3	Mitsubishi Dia Queen CVTF J1 / J4
Subaru e-CVTF	Subaru High Torque CVTF	Subaru Lineartronic CVTF / CVTF-II
Subaru i-CVT F / FG	Suzuki CVTF 3320	Suzuki CVT Fluid Green 1 / 2
Toyota TC	Toyota FE	Toyota WS (JWS3324)

Typical Analysis

Properties	Unit	Method	Typical Value
Color			Amber
Density @15°C	kg/m ³	ASTM D4052	848.7
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	34.3
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	7,0
Viscosity Index		ASTM D2270	174
Brookfield Viscosity @-40°C	cP	ASTM D2983	16000
Flash Point COC	°C	ASTM D92	>210
Pour Point	°C	ASTM D7346	-51

Date Issued: 31-12-2024	Supersedes: 09-03-2021	Revision Nr.: 02
-------------------------	------------------------	------------------