



## Form Oil 150

Mineral mould oil

Product Code: 78740

**Form Oil 150** is a high quality mineral moulding oil and is recommended for steel- and coated moulds and to be applied by spraying, swabbing or brushing and can also be used for the manufacturing of concrete in heated moulds

**Form Oil 150** is based on high quality mineral virgin base oil in combination with a special additive to ensure the following properties.

- Good release characteristics.
- No discoloring of the concrete surface.
- Good protection against deposits.
- High protection against rust in steel moulds at normal conditions.
- Preventing against put-forming in the concrete surface.
- No problems can be expected afterwards with tiles, wallpaper etc.
- Solvent Free, odourless.

### Typical Analysis

Properties	Unit	Method	Typical Value
ISO VG Class		ISO 3448	150
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	888.6
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	139.7
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-12
Total Acid Number	mg/KOH/g	ASTN D974	0.2

Date Issued: 14-1-2025	Supersedes: 26-04-2021	Revision Nr.: 1
------------------------	------------------------	-----------------