

Marine Oil DDC 40

Product Code: 77570

2-Stroke Mineral Marine Lubricant

Marine Oil DDC 40 is premium quality monograde engine oil developed for high output, high speed two-cycle diesel engines. This oil is designed to exceed the performance requirements of API CF/CF-2 and is particularly recommended for Detroit Diesel two-cycle diesel engines in marine fleets operating on low sulphur fuels.

Marine Oil DDC 40 is based on high quality mineral base stocks in combination with a special selected additive package to achieve to following properties.

- Excellent detergency reduces deposits, sludge build-up & varnish.
- Extend engine life & durability
- Superior thermo-oxidative stability.
- Improved antiwear technology protects against scuffing & wear of cylinder liner and walls
- Special rust inhibitors retard rust & corrosion formation in critical engine parts
- Adequate TBN levels ensure protection against corrosive combustion products

Marine Oil DDC 40 exceeds the following performance criteria:

API CF/CF-2

Typical Analysis

| Properties | | Unit | Method | | Typical Value |
|-----------------------|-----------|-------------------|------------------|---------|---------------|
| | | | | | |
| SAE Grade | | | SAE 2 | 13000 | SAE 40 |
| Density @15°C | | kg/m ³ | ASTM | I D4052 | 897.1 |
| Kin. Viscosity @40°C | | mm²/s | ASTM | I D7042 | 141.4 |
| Kin. Viscosity @100°C | | mm²/s | ASTM | I D7042 | 14.5 |
| Viscosity Index | | | ASTM | I D2270 | 101 |
| Flash Point COC | | °C | ASTM | I D92 | >220 |
| Pour Point | | °C | ASTM D7346 | | -21 |
| Total Base Number | | mgKOH/g | ASTM D2896 | | 12.2 |
| Sulphated Ash | | %Wt | ASTM D874 | | 0.8 |
| | | | | - | |
| Date Issued: 7-2-2025 | Supersede | s: 21-04-2021 | Revision Nr.: 03 | | |