



Engine Oil FSV 5W-30

Product Code: 76282

Synthetic Heavy Duty Diesel Engine Oil

Engine Oil FSV 5W-30 is a fuel saving MID SAPS, lowered HTHS, super high performance engine oil based on 100% synthetic technology designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year.

Engine Oil FSV 5W-30 is intended use in specific Euro-6 engines; please consult the owner's manual to check suitability.

Engine Oil FSV 5W-30 is formulated on high refined synthetic base stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against "Bore Polishing".
- Extended drain intervals up to 150.000 km.
- Suitable for engines equipped with a Diesel Particulate Filter (DPF).
- Fuel conserving

Engine Oil FSV 5W-30 exceeds the following performance criteria:

Approved:	Volvo VDS 5 DTFR 15C130	Mack EOS-5	Renault VI RLD-5
Exceeds:	API FA-4 JASO DH-2 Ford WSS-M2C214-B1	ACEA F01 Cummins CES 20087	API SN DDC 93K223

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-30
Density @15°C	kg/m ³	ASTM D4052	856
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	54.9
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	9.8
Viscosity Index		ASTM D2270	167
Viscosity CCS @-30°C	cP	ASTM D5293	5800
Flash Point COC	°C	ASTM D92	>200
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	9.8
HTHS @150°C	mPa*s	ASTM D4683	3.0

Date Issued: 27-05-2025	Supersedes: 25-04-2025	Revision Nr.: 01
-------------------------	------------------------	------------------