

Product Code: 79440

## **Motor Oil Synthetic DXI 5W-30**

Synthetic Passenger Car Motor Oil

**Motor Oil Synthetic DXI 5W-30** is the advanced synthetic energy conserving motor oil specially developed for the most modern high output gasoline and turbocharged engines in passenger cars, sport utility vehicles and light-duty trucks, operating on ethanol-containing fuels up to E85. It is formulated to help improve & retain fuel economy and protect vehicle emission system & turbocharger components while meeting the latest GM Dexos1 ™ demands.

**Motor Oil Synthetic DXI 5W-30** is based on high quality synthetic base oil in combination with a special selected additive package to reach to following properties:

- Improved protection against stochastic pre-ignition
- Improving sludge protection, piston cleanliness, turbo-charger protection, seal compatibility, wear protection
- Special friction modifiers used in this Energy conserving oil help improving & retaining fuel economy.
- Offers excellent lubrication at low temperatures and protect engine at high temperatures.
- Superior volatility characteristics reduce oil consumption and hydro-carbon pollution (VOCs).
- Advanced additive chemistry helps in emission system durability.
- Compatible with ethanol-containing fuels up to E85.

## Motor Oil Synthetic DXI 5W-30 meets the following performance criteria:

API SQ API SP API SN + RC ILSAC GF-7A Dexos1™ Gen 3 Ford WSS-M2C961-A1 GM 6094M GM 4718M Chrysler MS-6395 Chrysler MS-13340

## **Typical Analysis**

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-30
Density @15°C	kg/m³	ASTM D4052	848.1
Kin. Viscosity @40°C	mm²/s	ASTM D7042	58.8
Kin. Viscosity @100°C	mm²/s	ASTM D7042	10.6
Viscosity Index		ASTM D2270	171
Viscosity CCS -30°C	сР	ASTM D5293	3910
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	8.4

Date Issued: 7-10-2025 Supersedes: 12-2-2025 Revision Nr.: 04