

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : 78180 - MOTOR OIL LL-III 5W-30  
Product code : 78180

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses

Intended for general public  
Main use category : Industrial use, Professional use, Consumer use  
Function or use category : Lubricants and additives

#### 1.3. Details of the supplier of the safety data sheet

Transnational Blenders bv  
Wieldrechtseweg 37  
NL 3316 BG Dordrecht, Netherlands, Zuid Holland  
Netherlands  
T +31 (0)78 6527652  
[technical@tnb.nl](mailto:technical@tnb.nl), [www.tnb.nl](http://www.tnb.nl)

#### 1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

##### Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

No labelling applicable

#### 2.3. Other hazards

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

# 78180 - MOTOR OIL LL-III 5W-30

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH, TR); substance with a Community workplace exposure limit (Note L)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25	≥ 75 – < 90	Not classified
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil substance with a Community workplace exposure limit (Note L)	CAS-No.: 72623-87-1 EC-No.: 276-738-4 EC Index-No.: 649-483-00-5 REACH-no: 01-2119474889-13	≥ 1 – < 5	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed heavy paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH, TR); substance with a Community workplace exposure limit (Note L)	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6 REACH-no: 01-2119471299-27	≥ 1 – < 3	Asp. Tox. 1, H304
Distillates (petroleum), solvent-refined heavy paraffinic substance with national workplace exposure limit(s) (BE, BG, CZ, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH); substance with a Community workplace exposure limit (Note L)	CAS-No.: 64741-88-4 EC-No.: 265-090-8 EC Index-No.: 649-454-00-7 REACH-no: 01-2119488706-23	≥ 0.5 – < 3	Not classified
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased	CAS-No.: 122384-87-6 EC-No.: 701-251-5 REACH-no: 01-2119524004-56	≥ 0.5 – < 3	Aquatic Chronic 4, H413

Note L: The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.

Full text of H- and EUH-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
First-aid measures for first aider	: First aid workers will be equipped with suitable personal protective equipment.

# 78180 - MOTOR OIL LL-III 5W-30

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

### 5.3. Advice for firefighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	--

#### For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area.

#### For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment	: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

# 78180 - MOTOR OIL LL-III 5W-30

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Keep cool. Protect from sunlight.
Storage temperature	: ≤ 40 °C
Packaging materials	: Store always product in container of same material as original container.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

National occupational exposure and biological limit values

##### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)

###### EU - Indicative Occupational Exposure Limit (IOEL)

IOEL TWA	5 mg/m <sup>3</sup>
IOEL STEL	10 mg/m <sup>3</sup>

##### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

###### EU - Indicative Occupational Exposure Limit (IOEL)

IOEL TWA	5 mg/m <sup>3</sup>
IOEL STEL	10 mg/m <sup>3</sup>

###### Ireland - Occupational Exposure Limits

OEL TWA	5 ppm Form: inhalable fraction
---------	--------------------------------

##### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

###### EU - Indicative Occupational Exposure Limit (IOEL)

IOEL TWA	5 mg/m <sup>3</sup>
IOEL STEL	10 mg/m <sup>3</sup>

###### Ireland - Occupational Exposure Limits

OEL TWA	5 ppm Form: inhalable fraction
---------	--------------------------------

##### Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)

###### EU - Indicative Occupational Exposure Limit (IOEL)

IOEL TWA	5 mg/m <sup>3</sup>
IOEL STEL	10 mg/m <sup>3</sup>

###### Ireland - Occupational Exposure Limits

OEL TWA	5 ppm Form: inhalable fraction
---------	--------------------------------

# 78180 - MOTOR OIL LL-III 5W-30

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2. Exposure controls

#### Appropriate engineering controls

##### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### Personal protection equipment

##### Personal protective equipment:

Wear recommended personal protective equipment.

##### Personal protective equipment symbol(s):



#### Eye and face protection

##### Eye protection:

Safety glasses

#### Eye protection

Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

#### Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves

#### Hand protection

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	>0.35		EN ISO 374

#### Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### Environmental exposure controls

##### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light brown.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: -36 °C (ASTM D7346)
Boiling point	: Not available
Flammability	: Non flammable.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 201 °C (ASTM D92)
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available

# 78180 - MOTOR OIL LL-III 5W-30

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

pH	: Not available
Viscosity, kinematic	: 73.2 mm <sup>2</sup> /s @ 40°C (ASTM D7042)
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 852 kg/m <sup>3</sup> @ 15°C (ASTM D4052)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)

LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 2000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

LD50 oral (rat)	> 5000 mg/kg 401 Acute Oral Toxicity Test
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 oral (rat)	> 5000 mg/kg 401 Acute Oral Toxicity Test
-----------------	---

# 78180 - MOTOR OIL LL-III 5W-30

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5 mg/l/4h 403 Acute Inhalation Toxicity Test
<b>Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)</b>	
LD50 oral (rat)	> 5000 mg/kg 401 Acute Oral Toxicity
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity
<b>Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased (122384-87-6)</b>	
LD50 oral (rat)	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal (rabbit)	> 4000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 inhalation (rat) (mg/l)	> 1.67 mg/l OECD 403 (1h)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
<b>Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (subacute, oral, 28 days)	100 mg/kg bodyweight/day
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
<b>Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day
<b>Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased (122384-87-6)</b>	
NOAEL (oral, rat, 90 days)	200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (dermal, rat/rabbit, 90 days)	≈ 250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Aspiration hazard	: Not classified
<b>78180 - MOTOR OIL LL-III 5W-30</b>	
Viscosity, kinematic	73.2 mm²/s @ 40°C (ASTM D7042)

# 78180 - MOTOR OIL LL-III 5W-30

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)</b>	
Viscosity, kinematic	47 mm <sup>2</sup> /s
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
Viscosity, kinematic	150 (1.99 – 847) mm <sup>2</sup> /s @40°C
<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
Viscosity, kinematic	20.8 mm <sup>2</sup> /s @ 40°C
<b>Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)</b>	
Viscosity, kinematic	28.51 mm <sup>2</sup> /s @40°C
<b>Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased (122384-87-6)</b>	
Viscosity, kinematic	206820 mm <sup>2</sup> /s Temp.: '20°C' Parameter: 'cSt'

### 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

<b>Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)</b>	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 Daphnia magna
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)
NOEC chronic algae	100 mg/l Pseudokirchneriella subcapitata (72h)
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Pseudokirchneriella subcapitat (OECD 201)
NOEC chronic fish	> 1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)
NOEC chronic algae	100 mg/l Pseudokirchneriella subcapitata (72h)
<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata



# 78180 - MOTOR OIL LL-III 5W-30

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata (72h)

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased (122384-87-6)	
LC50 - Fish [1]	> 1000 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 1000 mg/l
EC50 96h - Algae [1]	> 500 mg/l Pseudokirchneriella subcapitata

### 12.2. Persistence and degradability

78180 - MOTOR OIL LL-III 5W-30	
Persistence and degradability	Not rapidly degradable

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)	
Persistence and degradability	Rapidly degradable.
Biodegradation	31 %

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	< 31 % OECD TG 301 F (28d)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	Not rapidly degradable
Biodegradation	< 31 % OECD TG 301 F (28d)

Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % OECD 301F (28d)

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased (122384-87-6)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	13.4 % OECD 301B - 28d

### 12.3. Bioaccumulative potential

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)	
Partition coefficient n-octanol/water (Log Pow)	> 6

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
Bioconcentration factor (BCF REACH)	260

Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)	
Partition coefficient n-octanol/water (Log Pow)	3.9 – 6

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased (122384-87-6)	
Partition coefficient n-octanol/water (Log Pow)	9.5

# 78180 - MOTOR OIL LL-III 5W-30

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.4. Mobility in soil

#### Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased (122384-87-6)

Mobility in soil	3615000000000 Source: EPISUITE
------------------	--------------------------------

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.
European List of Waste (LoW, EC 2000/532)	: 13 02 06* - synthetic engine, gear and lubricating oils

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
Not regulated for transport				
<b>14.2. UN proper shipping name</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.4. Packing group</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.5. Environmental hazards</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Not regulated

#### Transport by sea

Not regulated

#### Air transport

Not regulated

# 78180 - MOTOR OIL LL-III 5W-30

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Inland waterway transport

Not regulated

### Rail transport

Not regulated

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains substance(s) listed on the REACH Candidate List < 0.1% or SCL.

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

##### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

##### Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

##### Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level

# 78180 - MOTOR OIL LL-III 5W-30

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
H304	May be fatal if swallowed and enters airways.
H413	May cause long lasting harmful effects to aquatic life.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.