

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 23/08/2017 Revision date: 19/08/2025 Supersedes version of: 12/01/2024 Version: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : 79600 - Motor Oil Synth SL 0W-30

Product code : 79600

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Intended for general public

Main use category : Industrial use, Professional use, Consumer use

Function or use category : Lubricants and additives

1.3. Details of the supplier of the safety data sheet

Transnational Blenders bv
Wieldrechtseweg 37
NL 3316 BG Dordrecht, Netherlands, Zuid Holland
Netherlands
T +31 (0)78 6527652
technical@tnb.nl, www.tnb.nl

1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains C14-16-18 Alkyl phenol, Molybdenum polysulphide long chain alkyl

dithiocarbamate complex. May produce an allergic reaction.

EUH210 - Safety data sheet available on request.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1-decene,homopolymer,hydrogenated substance with national workplace exposure limit(s) (BG)	CAS-No.: 68037-01-4 EC-No.: 500-183-1 REACH-no: 01-2119486452- 34	< 55	Not classified
Distillates (petroleum), hydrotreated heavy paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH, TR); substance with a Community workplace exposure limit (Note L)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627- 25	≥ 25 – < 45	Not classified
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based substance with national workplace exposure limit(s) (BE, BG, CZ, DK, ES, FI, GR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SK, IS, NO, CH); substance with a Community workplace exposure limit (Note L)	CAS-No.: 72623-86-0 EC-No.: 276-737-9 EC Index-No.: 649-482-00-X REACH-no: 01-2119474878- 16	≥1-<3	Asp. Tox. 1, H304
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil substance with a Community workplace exposure limit (Note L)	CAS-No.: 72623-87-1 EC-No.: 276-738-4 EC Index-No.: 649-483-00-5 REACH-no: 01-2119474889- 13	≥1-<3	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed heavy paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH, TR); substance with a Community workplace exposure limit (Note L)	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6 REACH-no: 01-2119471299- 27	≥ 0.1 – < 3	Asp. Tox. 1, H304
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (Note L)	CAS-No.: 64742-70-7 EC-No.: 265-174-4 EC Index-No.: 649-477-00-2 REACH-no: 01-2119487080- 42	≥ 0.1 – < 3	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed light paraffinic substance with national workplace exposure limit(s) (BE, BG, CZ, DK, ES, FI, GR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SK, IS, NO, CH); substance with a Community workplace exposure limit (Note L)	CAS-No.: 64742-56-9 EC-No.: 265-159-2 EC Index-No.: 649-469-00-9 REACH-no: 01-2119480132- 48	≥ 0.1 – < 3	Not classified
zinc bis(O,O-diisooctyl) bis(dithiophosphate)	CAS-No.: 28629-66-5 EC-No.: 249-109-7 REACH-no: 01-2119953278- 28	≥ 0.3 – < 3	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411
C14-16-18 Alkyl phenol	EC-No.: 931-468-2 REACH-no: 01-2119498288- 19	≥ 0.1 – < 1	Skin Sens. 1B, H317 STOT RE 2, H373

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Molybdenum polysulphide long chain alkyl dithiocarbamate complex substance with national workplace exposure limit(s) (NL); substance with a Community workplace exposure limit	EC-No.: 457-320-2 REACH-no: 01-0000019337- 66	< 0.3	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Chronic 3, H412

Specific concentration limits:			
Name	Product identifier	Specific concentration limits (%)	
zinc bis(O,O-diisooctyl) bis(dithiophosphate)	CAS-No.: 28629-66-5 EC-No.: 249-109-7 REACH-no: 01-2119953278- 28	(15 ≤ C < 100) Eye Irrit. 2; H319 (15 ≤ C < 100) Eye Dam. 1; H318	

Note L:

The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

Self protection of the first-aider : First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : None under normal conditions. Symptoms/effects after skin contact : None under normal conditions. Symptoms/effects after eye contact : None under normal conditions. Symptoms/effects after ingestion : None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

Fire hazard : No fire hazard.

Explosion hazard : No direct explosion hazard. Hazardous decomposition products in case of fire : Toxic fumes may be released.

19/08/2025 (Revision date) IE - en 3/17

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.3. Advice for firefighters

Precautionary measures fire : Exercise caution when fighting any chemical fire.

Firefighting instructions : Use water spray or fog for cooling exposed containers. Do not enter fire area without proper

protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid spilling the product, as this might cause falls. Stop leak if safe to do so. Notify

authorities if product enters sewers or public waters. Absorb spillage to prevent material

damage.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams. Stop leak without risks if possible.

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Avoid

contact with skin and eyes.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Provide local exhaust or general room ventilation.

Storage conditions : Keep cool. Protect from sunlight.

Storage temperature : ≤ 40 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Keep only in original container. Store in a closed container.

Packaging materials : Store always product in container of same material as original container.

7.3. Specific end use(s)

No additional information available

19/08/2025 (Revision date) IE - en 4/17

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

and the state of t		
Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)	
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	5 mg/m³	
IOEL STEL	10 mg/m³	
Ireland - Occupational Exposure Limits		
OEL TWA	5 ppm Form: inhalable fraction	
Lubricating oils (petroleum), C15-30, hydrotre	ated neutral oil-based (72623-86-0)	
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	5 mg/m³	
Ireland - Occupational Exposure Limits		
OEL TWA	5 ppm Form: Inhalable fraction	
Distillates (petroleum), solvent-dewaxed heav	y paraffinic (64742-65-0)	
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	5 mg/m³	
IOEL STEL	10 mg/m³	
Ireland - Occupational Exposure Limits		
OEL TWA	5 ppm Form: inhalable fraction	
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	5 mg/m³ ACGIH TLV (inhalable fraction)	
Ireland - Occupational Exposure Limits		
OEL TWA	5 ppm Form: inhalable fraction	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	5 mg/m³	
IOEL STEL	10 mg/m³	
Molybdenum polysulphide long chain alkyl dithiocarbamate complex		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	5 mg/m³	
IOEL STEL	10 mg/m³	

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Personal protection equipment

Personal protective equipment:

Gloves. Safety glasses. Protective clothing. Personal protective equipment symbol(s):







Eye and face protection

Eye protection:

Safety glasses

Eye protection			
Туре	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	>0.35		EN ISO 374

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : light brown. Odour : Not available Odour threshold : Not available : Not applicable Melting point : -51 °C (ASTM D7346) Freezing point : Not available Boiling point Flammability : Non flammable.

Flammability : Non flammable.

Lower explosion limit : Not available

Upper explosion limit : Not available

Flash point : > 210 °C (ASTM D92)

Auto-ignition temperature : Not available
Decomposition temperature : Not available
pH : Not available

Viscosity, kinematic : 66.7 mm²/s @ 40°C (ASTM D7042)

Solubility : insoluble in water.

Partition coefficient n-octanol/water (Log Kow) : Not available

Vapour pressure : Not available

19/08/2025 (Revision date) IE - en 6/17

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Vapour pressure at 50°C : Not available

Density : 843 kg/m³ @ 15°C (ASTM D4052)

Relative density : Not available
Relative vapour density at 20°C : Not available
Particle characteristics : Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (inhalation)	: Not classified		
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)			
LD50 oral (rat)	> 5000 mg/kg 401 Acute Oral Toxicity Test		
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test		
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5 mg/l/4h 403 Acute Inhalation Toxicity Test		
1-decene,homopolymer,hydrogenated (680	037-01-4)		
LD50 oral (rat)	> 5000 mg/kg		
LD50 dermal (rat)	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)		
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.2 mg/l/4h		
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)			
LD50 oral (rat)	> 5000 mg/kg bodyweight 401 Acute Oral Toxicity Test		
LD50 dermal (rabbit)	> 2000 mg/kg 402 Acute Dermal Toxicity Test		
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test		

Safety Data Sheet

C14-16-18 Alkyl phenol	
LD50 oral (rat)	> 2000 mg/kg bodyweight
LD50 dermal (rat)	> 2000 mg/kg
Distillates (petroleum), solvent-dewaxed heav	ry paraffinic (64742-65-0)
LD50 oral (rat)	> 5000 mg/kg 401 Acute Oral Toxicity Test
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test
Paraffin oils (petroleum), catalytic dewaxed h	eavy; Baseoil (64742-70-7)
LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 2000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	5 mg/l/4h
Distillates (petroleum), solvent-dewaxed light	paraffinic (64742-56-9)
LD50 oral (rat)	> 5000 mg/kg 401 Acute Oral Toxicity Test
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test
Lubricating oils (petroleum), C20-50, hydrotre	eated neutral oil (72623-87-1)
LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 2000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h
zinc bis(O,O-diisooctyl) bis(dithiophosphate)	(28629-66-5)
LD50 oral (rat)	> 3760 mg/kg OECD Test Guideline 401
LD50 dermal (rabbit)	> 5000 mg/kg OECD Test Guideline 402
Molybdenum polysulphide long chain alkyl di	thiocarbamate complex
LD50 oral (rat)	> 2000 mg/kg OECD Test Guideline 425
LD50 dermal (rat)	> 2000 mg/kg OECD Test Guideline 402
Skin corrosion/irritation :	Not classified
Serious eye damage/irritation : Respiratory or skin sensitisation :	Not classified Not classified
Germ cell mutagenicity :	Not classified
Carcinogenicity :	Not classified
Reproductive toxicity :	Not classified
zinc bis(O,O-diisooctyl) bis(dithiophosphate)	(28629-66-5)
NOAEL (animal/male, F1)	160 mg/kg OECD Test Guideline 422
Molybdenum polysulphide long chain alkyl di	thiocarbamate complex
NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight
5 .	Not classified Not classified
Distillates (petroleum), hydrotreated heavy pa	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Safety Data Sheet

NOAEL (caral, rat, 90 days) 125 mg/kg bodyweight (caral, rat, 90 days) 126 mg/kg bodyweight (caral, rat, 90 days) 1270T-typeabed exposure May cause damage to organs (liver) through prolonged or repeated exposure. Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight Airmat, Animal sex; male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) NOAEL (subacute, oral, 28 days) 100 mg/kg bodyweight Airmat, rabbit, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) NOAEL (dermal, rat/rabbit, 90 days) 125 mg/kg bodyweight Airmat, rabbit, Guideline: OECD Guideline 410 (Repeated Dose Damal Toxicity, 21/28-Day Shudy) Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Rodents) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweightiday 2inc bis(O,O-dilisooctyl) bis(dithlophosphate) (28629-66-5) NOAEL (oral, rat, 90 days) 160 mg/kg bodyweightiday Molybdenum polysulphide long chain alkyl dithlocarbamate complex NOAEL (oral, rat, 90 days) 1000 mg/kg bodyweightiday OECD Test Guideline 410 Aspiration hazard 1000 mg/kg bodyweightiday OECD Test Guideline 410 Aspiration hazard 1000 mg/kg bodyweightiday OECD Test Guideline 410 Aspiration hazard 1000 mg/kg bodyweightiday OECD Test Guideline 410 Aspiration hazard 1000 mg/kg bodyweightiday OECD Test Guideline 410 Aspiration hazard 1000 mg/kg bodyweightiday OECD Test Guideline 410 Aspiration hazard 1000 mg/kg bodyweightiday OECD Test Guideline 410 Aspiration hazard 1000 mg/kg bodyweightiday OECD Test Guideline 410 1000 mg/kg bodyweightiday OECD Test Guideline 410 1000 mg/kg bodyweightiday OECD Test G	1-decene,homopolymer,hydrogenated (68037-01-4)			
NOAEL (oral, rat, 90 days) NOAEL (oral, rat, 90 days) Libricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight C14-16-18 Alkyl phenol STOT-repeated exposure May cause damage to organs (liver) through prolonged or repeated exposure. Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) LOAEL (oral, rat, 90 days) NOAEL (aubacute, oral, 28 days) NOAEL (dermal, rat/rabbit, 90 days) Distillates (petroleum), solvent-dewaxed light paraffinic (64742-55-9) LOAEL (oral, rat, 90 days) Paraffinic (54742-55-9) LOAEL (oral, rat, 90 days) LOAEL (oral, rat, 90 days) LUDAEL (oral, rat,				
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) LOAEL (oral, rat, 80 days) 125 mg/kg bodyweight C14-16-18 Alkyl phenol STOT-repeated exposure May cause damage to organs (liver) through prolonged or repeated exposure. Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-85-0) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight Animat: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) NOAEL (subacute, oral, 28 days) 100 mg/kg bodyweight (arimati: ratbit), Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweightiday NOAEL (oral, rat, 90 days) 125 mg/kg bodyweightiday NOAEL (oral, rat, 90 days) 160 mg/kg bodyweightiday NOAEL (oral, rat, 90 days) NOAEL (oral, rat, 90 days) 1000 mg/kg bodyweightiday OECD Test Guideline 407 NOAEL (oral, rat, 90 days) NOAEL (oral, rat, 90 days) NOAEL (oral, rat, 90 days) 1000 mg/kg bodyweightiday OECD Test Guideline 407 NOAEL (oral, rat, 90 days) NOAEL (oral, rat, 90 days) NOAEL (oral, rat, 90 days) 867 mg/kg bodyweightiday OECD Test Guideline 407 NOAEL (oral, rat, 90 days) 1000 mg/kg bodyweightiday OECD Test Guideline 407 NOAEL (oral, rat, 90 days) NOAEL (oral, rat,	, , ,			
LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight C14-16-18 Alkyl phenol STOT-repealed exposure May cause damage to organs (liver) through prolonged or repealed exposure. Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight (Aminal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Does 90-Day Oral Toxicity in Rodents) NOAEL (subacute, oral, 28 days) NOAEL (dermal, rat/rabbit, 90 days) Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9) LOAEL (oral, rat, 90 days) Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight (OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day Zinc bis(Q,O-diisooctyl) bis(dithiophosphate) (28629-66-5) NOAEL (oral, rat, 90 days) 160 mg/kg bodyweight/day Molybdenum polysulphide long chain alkyl dithiocarbamate complex NOAEL (oral, rat, 90 days) 1000 mg/kg bodyweight/day OECD Test Guideline 407 NOAEL (oral, rat, 90 days) 1000 mg/kg bodyweight/day OECD Test Guideline 407 NOAEL (oral, rat, 90 days) 1000 mg/kg bodyweight/day OECD Test Guideline 407 NOAEL (oral, rat, 90 days) 7500 mg/kg bodyweight/day OECD Test Guideline 407 NoAEL (oral, rat, 90 days) Viscosity, kinematic 66.7 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 20.8 mm²/s @ 40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 52 mm²/s @ 40°C C14-16-18 Alkyl phenol Viscosity, kinematic 52 mm²/s @ 40°C Distillates (petroleum), catalytic dewaxed heavy; Bassoil (64742-70-7)				
C14-16-18 Alkyl phenol STOT-repeated exposure May cause damage to organs (liver) through prolonged or repeated exposure. Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) LOAEL (oral, rat, 90 daye) (25 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 99-Day Oral Toxicity in Rodents) NOAEL (subacuta, oral, 28 days) 100 mg/kg bodyweight Animal: ratbolt, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) NOAEL (dermal, rat/rabbit, 90 days) +100 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day Inc bis(O,O-dilisooctyl) bis(dithiophosphate) (28629-66-5) NOAEL (oral, rat, 90 days) 100 mg/kg bodyweight/day Molybdonum polysulphide long chain alkyl dithiocarbamate complex NOAEL (oral, rat, 90 days) 1000 mg/kg bodyweight/day OECD Test Guideline 407 NOAEL (oral, rat, 90 days) 670 mg/kg bodyweight/day OECD Test Guideline 410 Aspiration hazard : Not classified 79500 - Motor Oil Synth SL 0W-30 Viscosity, kinematic 66.7 mm/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 46000000 mm/s @ 40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 52 mm/s @ 40°C Distillates (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)				
STOT-repeated exposure May cause damage to organs (liver) through prolonged or repeated exposure. Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) NOAEL (subacute, oral, 28 days) 100 mg/kg bodyweight/day NOAEL (dermal, rat/rabbit, 90 days) - 1000 mg/kg bodyweight/day Study) Distillates (petroleum), solvent-dewaxed light paraffinic (64742-55-9) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day zinc bis(O,O-diisooctyl) bis(dithiophosphate) (28629-66-5) NOAEL (oral, rat, 90 days) 1000 mg/kg bodyweight/day Molybdenum polysulphide long chain alkyl dithiocarbamate complex NOAEL (oral, rat, 90 days) 1000 mg/kg bodyweight/day OECD Test Guideline 407 NOAEL (oral, rat, 90 days) 670 mg/kg bodyweight/day OECD Test Guideline 410 Aspiration hazard Notasified Notasified 1980 Molybdenum polysulphide long chain alkyl dithiocarbamate complex NOAEL (oral, rat, 90 days) 670 mg/kg bodyweight/day OECD Test Guideline 410 Aspiration hazard Notasified Notasified 1980 Molybdenum polysulphide long chain alkyl dithiocarbamate complex NOAEL (oral, rat, 90 days) 670 mg/kg bodyweight/day OECD Test Guideline 410 Aspiration hazard Notasified Notasified 1980 Molybdenum polysulphide Notasified 1980 Molybdenum polys		125 mg/kg boayweight		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) LOAEL (oral, rat, 90 days) (Repeated Dose 90-Day Oral Toxicity in Rodents) NOAEL (subacute, oral, 28 days) 100 mg/kg bodyweight Animal: rat Animal sex: mate, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) NOAEL (dermal, rat/rabbit, 90 days) * 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9) LOAEL (oral, rat, 90 days) (125 mg/kg bodyweight OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1) LOAEL (oral, rat, 90 days) (125 mg/kg bodyweight/day zinc bis(0,0-dilisooctyl) bis(dithiophosphate) (28629-66-5) NOAEL (oral, rat, 90 days) (160 mg/kg bodyweight/day) Molybdenum polysulphide long chain alkyl dithiocarbamate complex NOAEL (oral, rat, 90 days) (1000 mg/kg bodyweight/day OECD Test Guideline 407 NOAEL (dermal, rat/rabbit, 90 days) (570 mg/kg bodyweight/day OECD Test Guideline 410 Aspiration hazard : Not classified 79800 - Motor OII Synth SL 0W-30 Viscosity, kinematic (64742-54-7) Viscosity, kinematic (20 8 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic (2978 mm²/s @ 40°C C14-16-18 Alkyl phenol Viscosity, kinematic (2978 mm²/s @ 40°C C14-16-18 Alkyl phenol Viscosity, kinematic (20 9 mm²/s @ 40°C C14-16-18 Alkyl phenol Viscosity, kinematic (20 9 mm²/s @ 40°C Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic (20 9 mm²/s @ 40°C Paraffin oils (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic (20 9 mm²/s @ 40°C Paraffin oils (petroleum), solvent-dewaxed heavy paraffinic (64742-70-7)				
LOAEL (oral, rat, 90 days) (Repeated Dose 90-Day Oral Toxicity in Rodents) NOAEL (subacute, oral, 28 days) NOAEL (dermal, rat/rabbit, 90 days) 100 mg/kg bodyweight/day 100 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose Dermal Toxicity in Rodents) NOAEL (dermal, rat/rabbit, 90 days) 110 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day It25 mg/kg bodyweight/day It25 mg/kg bodyweight/day It25 mg/kg bodyweight/day It26 mg/kg bodyweight/day It26 mg/kg bodyweight/day It26 mg/kg bodyweight/day It26 mg/kg bodyweight/day It27 mg/kg bodyweight/day It28	STOT-repeated exposure	May cause damage to organs (liver) through prolonged or repeated exposure.		
Repeated Dose 90-Day Oral Toxicity in Rodents NOAEL (subacute, oral, 28 days) 100 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) Distillates (potroleum), solvent-dowaxed light paraffinic (64742-56-9) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day Zinc bis(O,O-diisooctyl) bis(dithiophosphate) (28629-66-5) NOAEL (oral, rat, 90 days) 160 mg/kg bodyweight/day Molybdenum polysulphide long chain alkyl dithiocarbamate complex NOAEL (dermal, rat/rabbit, 90 days) 1000 mg/kg bodyweight/day OECD Test Guideline 407 NOAEL (dermal, rat/rabbit, 90 days) 670 mg/kg bodyweight/day OECD Test Guideline 410 Aspiration hazard Not classified 79600 - Motor Oil Synth St. 0W-30 Viscosity, kinematic 66.7 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 20.8 mm²/s @ 40°C 24-16-18 Alkyl phenol 2978 mm²/s @ 40°C 2978 mm²/s @ 40°C 24-16-18 Alkyl phenol 2978 mm²/s @ 40°C 24-16-18 Alkyl phenol 2978 mm²/s @ 40°C 24-16-18 Alkyl phenol 250 mg/kg @ 40°C 24-16-19 mm²/s @ 40°C	Distillates (petroleum), solvent-dewaxed hea	vy paraffinic (64742-65-0)		
NOAEL (dermal, rat/rabbit, 90 days) Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day zinc bis(O,O-diisooctyl) bis(dithiophosphate) (28629-66-5) NOAEL (oral, rat, 90 days) 160 mg/kg bodyweight/day Zinc bis(O,O-diisooctyl) bis(dithiophosphate) (28629-66-5) NOAEL (oral, rat, 90 days) NOAEL (dermal, rat/rabbit, 90 days) NOAEL (dermal, rat/rabb	LOAEL (oral, rat, 90 days)			
Dermal Toxicity: 21/28-Day Study) Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9) LOAEL (oral, rat, 90 days)	NOAEL (subacute, oral, 28 days)	100 mg/kg bodyweight/day		
LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day Zinc bis(O,O-diisooctyl) bis(dithiophosphate) (28629-66-5) NOAEL (oral, rat, 90 days) 160 mg/kg bodyweight/day Molybdenum polysulphide long chain alkyl dithiocarbamate complex NOAEL (oral, rat, 90 days) 1000 mg/kg bodyweight/day OECD Test Guideline 407 NOAEL (dermal, rat/rabbit, 90 days) 670 mg/kg bodyweight/day OECD Test Guideline 410 Aspiration hazard: Not classified 79600 - Motor Oil Synth SL 0W-30 Viscosity, kinematic: 66.7 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic: 20.8 mm²/s @ 40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic: 52 mm²/s @40°C C14-16-18 Alkyl phenol Viscosity, kinematic: 52 mm²/s @40°C Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic: 150 (1.99 – 847) mm²/s @40°C Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	NOAEL (dermal, rat/rabbit, 90 days)			
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1) LOAEL (oral, rat, 90 days) Zinc bis(O,O-diisooctyl) bis(dithiophosphate) (28629-66-5) NOAEL (oral, rat, 90 days) Molybdenum polysulphide long chain alkyl dithiocarbamate complex NOAEL (oral, rat, 90 days) NOAEL (oral, rat, 90 days) Molybdenum polysulphide long chain alkyl dithiocarbamate complex NOAEL (oral, rat, 90 days) NOAEL (dermal, rat/rabbit, 90 days) NOAEL (dermal, rat/rabbit, 90 days) NOAEL (dermal, rat/rabbit, 90 days) For mg/kg bodyweight/day OECD Test Guideline 410 Aspiration hazard Not classified 79600 - Motor Oil Synth SL 0W-30 Viscosity, kinematic Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 20.8 mm²/s @ 40°C 1-decene,homopolymer,hydrogenated (68037-01-4) Viscosity, kinematic 46000000 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 52 mm²/s @ 40°C C14-16-18 Alkyl phenol Viscosity, kinematic 52 mm²/s @40°C Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic 150 (1.99 – 847) mm²/s @40°C Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	Distillates (petroleum), solvent-dewaxed ligh	t paraffinic (64742-56-9)		
LOAEL (oral, rat, 90 days) zinc bis(O,O-diisooctyl) bis(dithiophosphate) (28629-66-5) NOAEL (oral, rat, 90 days) Molybdenum polysulphide long chain alkyl dithiocarbamate complex NOAEL (oral, rat, 90 days) NOAEL (dermal, rat/rabbit, 90 days) NOAEL (dermal, rat/rabbit, 90 days) NOAEL (dermal, rat/rabbit, 90 days) Septimental of the septiment of the septim	LOAEL (oral, rat, 90 days)			
zinc bis(O,O-diisooctyl) bis(dithiophosphate) (28629-66-5) NOAEL (oral, rat, 90 days) 160 mg/kg bodyweight/day Molybdenum polysulphide long chain alkyl dithiocarbamate complex NOAEL (oral, rat, 90 days) 1000 mg/kg bodyweight/day OECD Test Guideline 407 NOAEL (dermal, rat/rabbit, 90 days) 670 mg/kg bodyweight/day OECD Test Guideline 410 Aspiration hazard : Not classified 79600 - Motor Oil Synth SL 0W-30 Viscosity, kinematic 66.7 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 20.8 mm²/s @ 40°C 1-decene,homopolymer,hydrogenated (68037-01-4) Viscosity, kinematic 46000000 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 2978 mm²/s 40°C C14-16-18 Alkyl phenol Viscosity, kinematic 52 mm²/s @40°C Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic 150 (1.99 – 847) mm²/s @40°C Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	Lubricating oils (petroleum), C20-50, hydrotr	reated neutral oil (72623-87-1)		
MOJAEL (oral, rat, 90 days) Molybdenum polysulphide long chain alkyl dithiocarbamate complex NOAEL (oral, rat, 90 days) 1000 mg/kg bodyweight/day OECD Test Guideline 407 NOAEL (dermal, rat/rabbit, 90 days) 670 mg/kg bodyweight/day OECD Test Guideline 410 Aspiration hazard : Not classified 79600 - Motor Oil Synth SL 0W-30 Viscosity, kinematic 66.7 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 20.8 mm²/s @ 40°C 1-decene,homopolymer,hydrogenated (68037-01-4) Viscosity, kinematic 46000000 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 2978 mm²/s @40°C C14-16-18 Alkyl phenol Viscosity, kinematic 52 mm²/s @40°C Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic 52 mm²/s @40°C Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day		
Molybdenum polysulphide long chain alkyl dithiocarbamate complex NOAEL (oral, rat, 90 days) 1000 mg/kg bodyweight/day OECD Test Guideline 407 NOAEL (dermal, rat/rabbit, 90 days) 670 mg/kg bodyweight/day OECD Test Guideline 410 Aspiration hazard: Not classified 79600 - Motor Oil Synth SL 0W-30 Viscosity, kinematic: 66.7 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic: 20.8 mm²/s @ 40°C 1-decene,homopolymer,hydrogenated (68037-01-4) Viscosity, kinematic: 46000000 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic: 2978 mm²/s 40°C C14-16-18 Alkyl phenol Viscosity, kinematic: 52 mm²/s @40°C Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic: 150 (1.99 – 847) mm²/s @40°C Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	zinc bis(O,O-diisooctyl) bis(dithiophosphate) (28629-66-5)		
NOAEL (oral, rat, 90 days) 1000 mg/kg bodyweight/day OECD Test Guideline 407 NOAEL (dermal, rat/rabbit, 90 days) 670 mg/kg bodyweight/day OECD Test Guideline 410 Aspiration hazard: Not classified 79600 - Motor Oil Synth SL 0W-30 Viscosity, kinematic: 66.7 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic: 20.8 mm²/s @ 40°C 1-decene,homopolymer,hydrogenated (68037-01-4) Viscosity, kinematic: 46000000 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic: 2978 mm²/s 40°C C14-16-18 Alkyl phenol Viscosity, kinematic: 52 mm²/s @40°C Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic: 150 (1.99 – 847) mm²/s @40°C Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	NOAEL (oral, rat, 90 days)	160 mg/kg bodyweight/day		
NOAEL (dermal, rat/rabbit, 90 days) 670 mg/kg bodyweight/day OECD Test Guideline 410 Aspiration hazard : Not classified 79600 - Motor Oil Synth SL 0W-30 Viscosity, kinematic 66.7 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 20.8 mm²/s @ 40°C 1-decene,homopolymer,hydrogenated (68037-01-4) Viscosity, kinematic 46000000 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 2978 mm²/s 40°C C14-16-18 Alkyl phenol Viscosity, kinematic 52 mm²/s @40°C Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic 150 (1.99 – 847) mm²/s @40°C Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	Molybdenum polysulphide long chain alkyl dithiocarbamate complex			
Aspiration hazard : Not classified 79600 - Motor Oil Synth SL 0W-30 Viscosity, kinematic 66.7 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 20.8 mm²/s @ 40°C 1-decene,homopolymer,hydrogenated (68037-01-4) Viscosity, kinematic 46000000 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 2978 mm²/s 40°C C14-16-18 Alkyl phenol Viscosity, kinematic 52 mm²/s @40°C Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic 150 (1.99 – 847) mm²/s @40°C Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight/day OECD Test Guideline 407		
Viscosity, kinematic Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 20.8 mm²/s @ 40°C 1-decene,homopolymer,hydrogenated (68037-01-4) Viscosity, kinematic 46000000 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 2978 mm²/s 40°C C14-16-18 Alkyl phenol Viscosity, kinematic 52 mm²/s @40°C Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic 150 (1.99 – 847) mm²/s @40°C Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	NOAEL (dermal, rat/rabbit, 90 days)	670 mg/kg bodyweight/day OECD Test Guideline 410		
Viscosity, kinematic Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 20.8 mm²/s @ 40°C 1-decene,homopolymer,hydrogenated (68037-01-4) Viscosity, kinematic 46000000 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 2978 mm²/s 40°C C14-16-18 Alkyl phenol Viscosity, kinematic 52 mm²/s @40°C Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic 150 (1.99 – 847) mm²/s @40°C Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	Aspiration hazard :	Not classified		
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 20.8 mm²/s @ 40°C 1-decene,homopolymer,hydrogenated (68037-01-4) Viscosity, kinematic 46000000 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 2978 mm²/s 40°C C14-16-18 Alkyl phenol Viscosity, kinematic 52 mm²/s @40°C Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic 150 (1.99 – 847) mm²/s @40°C Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	79600 - Motor Oil Synth SL 0W-30			
Viscosity, kinematic 1-decene,homopolymer,hydrogenated (68037-01-4) Viscosity, kinematic 46000000 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 2978 mm²/s 40°C C14-16-18 Alkyl phenol Viscosity, kinematic 52 mm²/s @40°C Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic 150 (1.99 – 847) mm²/s @40°C Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	Viscosity, kinematic	66.7 mm²/s @ 40°C (ASTM D7042)		
1-decene,homopolymer,hydrogenated (68037-01-4) Viscosity, kinematic 46000000 mm²/s @40°C Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 2978 mm²/s 40°C C14-16-18 Alkyl phenol Viscosity, kinematic 52 mm²/s @40°C Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic 150 (1.99 – 847) mm²/s @40°C Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	Distillates (petroleum), hydrotreated heavy p	araffinic (64742-54-7)		
Viscosity, kinematic Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 2978 mm²/s 40°C C14-16-18 Alkyl phenol Viscosity, kinematic 52 mm²/s @40°C Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic 150 (1.99 – 847) mm²/s @40°C Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	Viscosity, kinematic	20.8 mm²/s @ 40°C		
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0) Viscosity, kinematic 2978 mm²/s 40°C C14-16-18 Alkyl phenol Viscosity, kinematic 52 mm²/s @40°C Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic 150 (1.99 – 847) mm²/s @40°C Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	1-decene,homopolymer,hydrogenated (6803	7-01-4)		
Viscosity, kinematic 2978 mm²/s 40°C C14-16-18 Alkyl phenol Viscosity, kinematic 52 mm²/s @40°C Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic 150 (1.99 – 847) mm²/s @40°C Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	Viscosity, kinematic	46000000 mm²/s @40°C		
C14-16-18 Alkyl phenol Viscosity, kinematic 52 mm²/s @40°C Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic 150 (1.99 – 847) mm²/s @40°C Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	Lubricating oils (petroleum), C15-30, hydrotr	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)		
Viscosity, kinematic Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic 150 (1.99 – 847) mm²/s @40°C Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	Viscosity, kinematic	2978 mm²/s 40°C		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic 150 (1.99 – 847) mm²/s @40°C Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	C14-16-18 Alkyl phenol			
Viscosity, kinematic 150 (1.99 – 847) mm²/s @40°C Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	Viscosity, kinematic	52 mm²/s @40°C		
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	Distillates (petroleum), solvent-dewaxed hea	vy paraffinic (64742-65-0)		
	Viscosity, kinematic	150 (1.99 – 847) mm²/s @40°C		
Viscosity, kinematic 19 mm²/s @40°C	Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)			
	Viscosity, kinematic	19 mm²/s @40°C		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)		
Viscosity, kinematic	1.99 – 847 mm²/s Temp.: '40°C	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)		
Viscosity, kinematic	47 mm²/s	
zinc bis(O,O-diisooctyl) bis(dithiophosphate) (28629-66-5)		
Viscosity, kinematic 130.6 mm²/s @ 40°C (ASTM D445-97)		

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse

effects in the environment.

Hazardous to the aquatic environment, short–term

(acute)

: Not classified

: Not classified

Hazardous to the aquatic environment, long-term

(chronic)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata

1-decene,homopolymer,hydrogenated (68037-01-4)		
LC50 - Fish [1]	> 1000 mg/l Rainbow trout	
EC50 - Crustacea [1]	> 1000 mg/l Daphnia magna	
EC50 72h - Algae [1]	> 1000 mg/l Scenedesmus quadricauda	
NOEC chronic crustacea	125 mg/l Daphnia magna (21d)	
NOEC chronic algae	> 1000 mg/l Scenedesmus quadricauda (3h)	

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
LC50 - Fish [1] > 100 mg/l Pimephales promelas (OECD 203)	
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna (OECD 202)
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata (72h)
C14-16-18 Alkyl phenol	

C14-16-18 Alkyl phenol	
LC50 - Fish [1]	> 100 mg/l Cyprinus carpio
EC50 - Crustacea [1]	> 100 mg/l Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Selenastrum capricornutum
NOEC chronic algae	100 mg/l Selenastrum capricornutum (72h)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

3 3 (1, 11 1 1 1 1		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)		
LC50 - Fish [1]	> 100 mg/l Pimephales promelas	
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna	
EC50 72h - Algae [1]	> 100 mg/l Pseudokirchneriella subcapitat (OECD 201)	
NOEC chronic fish	> 1000 mg/l Oncorhynchus mykiss (14d)	
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)	
NOEC chronic algae	100 mg/l Pseudokirchneriella subcapitata (72h)	
Distillates (petroleum), solvent-dewaxed	l light paraffinic (64742-56-9)	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas (OECD 203)	
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna (OECD 202)	
NOEC chronic fish	≥ 1000 mg/l Oncorhynchus mykiss	
NOEC chronic crustacea	> 10 mg/l Daphnia magna (21d) (OECD 211)	
NOEC chronic algae	> 100 mg/l Pseudokirchneriella subcapitata (72h) (OECD 201)	
Lubricating oils (petroleum), C20-50, hyd	drotreated neutral oil (72623-87-1)	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas	
EC50 - Crustacea [1]	> 10000 Daphnia magna	
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)	
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)	
NOEC chronic algae	100 mg/l Pseudokirchneriella subcapitata (72h)	
zinc bis(O,O-diisooctyl) bis(dithiophosp	hate) (28629-66-5)	
LC50 - Fish [1]	3.8 mg/l OECD 203 (Oncorhynchus mykiss)	
EC50 - Crustacea [1]	510 mg/l OECD 202 (Daphnia magna)	
EC50 72h - Algae [1]	240 mg/l Desmodesmus subspicatus OECD Test Guideline 201	
NOEC chronic fish	1.8 mg/l OECD 203 (Oncorhynchus mykiss)	
Molybdenum polysulphide long chain alkyl dithiocarbamate complex		
LC50 - Fish [1]	> 94.8 mg/l Oncorhynchus mykiss (OECD 203)	
LC50 - Fish [2]	> 670 mg/l Oncorhynchus mykiss (OECD 203)	
EC50 - Crustacea [1]	50 mg/l Daphnia magna (OECD 202)	
EC50 72h - Algae [1]	14 mg/l Pseudokirchneriella subcapitata (OECD 201)	
NOEC (chronic)	100 mg/l	
NOEC chronic fish	94.8 mg/l (Oncorhynchus mykiss (rainbow trout) OECD Test Guideline 203 (96h)	
NOEC chronic crustacea	100 mg/l Daphnia magna (21d) (OECD 211)	
NOEC chronic algae	4.05 mg/l	

12.2. Persistence and degradability

79600 - Motor Oil Synth SL 0W-30		
Persistence and degradability	Rapidly degradable	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Persistence and degradability	Not rapidly degradable	

Safety Data Sheet

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Biodegradation	< 31 % OECD TG 301 F (28d)	
1-decene,homopolymer,hydrogenated (68037-01-4)		
Persistence and degradability	Not readily biodegradable.	
Biodegradation	2 % OECD TG 301 D (28d)	
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)		
Persistence and degradability	Not readily biodegradable.	
Biodegradation	31 % 28 d OECD 301F	
C14-16-18 Alkyl phenol		
Persistence and degradability	Not readily biodegradable.	
Biodegradation	6 % OECD TG 301 B (28d)	
Distillates (petroleum), solvent-dewaxed heav	y paraffinic (64742-65-0)	
Persistence and degradability	Not readily biodegradable.	
Biodegradation	< 31 % OECD TG 301 F (28d)	
Paraffin oils (petroleum), catalytic dewaxed h	eavy; Baseoil (64742-70-7)	
Persistence and degradability	Rapidly degradable.	
Distillates (petroleum), solvent-dewaxed light	paraffinic (64742-56-9)	
Persistence and degradability	Rapidly degradable.	
Biodegradation	31 % OECD TG 301 F (28d)	
Lubricating oils (petroleum), C20-50, hydrotre	eated neutral oil (72623-87-1)	
Persistence and degradability	Rapidly degradable.	
Biodegradation	31 %	
zinc bis(O,O-diisooctyl) bis(dithiophosphate)	(28629-66-5)	
Persistence and degradability	Not readily biodegradable.	
Biodegradation	< 5 % 28 d OECD Test Guideline 301D	
Molybdenum polysulphide long chain alkyl di	thiocarbamate complex	
Persistence and degradability	Not readily biodegradable.	
Biodegradation	23 % OECD Test Guideline 301B (29d)	
12.3. Bioaccumulative potential		
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Partition coefficient n-octanol/water (Log Pow)	2 – 6	
1-decene,homopolymer,hydrogenated (68037-01-4)		
Partition coefficient n-octanol/water (Log Pow)	> 6.5 @ 20°C	
C14-16-18 Alkyl phenol		
Partition coefficient n-octanol/water (Log Kow)	> 7.2	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)		
Bioconcentration factor (BCF REACH)	260	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)			
Partition coefficient n-octanol/water (Log Pow) > 6			
zinc bis(O,O-diisooctyl) bis(dithiophosphate) (28629-66-5)			
Partition coefficient n-octanol/water (Log Pow) 2.87 @ 20°C			
Molybdenum polysulphide long chain alkyl dithiocarbamate complex			
BCF - Fish [1]	0.05 mg/l @ 25°C (Cyprinus carpio)		
Bioconcentration factor (BCF REACH)	88 OECD TG 305 (8w)		
Partition coefficient n-octanol/water (Log Pow) 5.1 @ 20°C			

12.4. Mobility in soil

1-decene,homopolymer,hydrogenated (68037-01-4)		
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	> 6.2	
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)		
Ecology - soil	Adsorbs into the soil.	
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)		
Ecology - soil	Adsorbs into the soil.	
zinc bis(O,O-diisooctyl) bis(dithiophosphate) (28629-66-5)		
Ecology - soil	Adsorbs into the soil.	
Molybdenum polysulphide long chain alkyl dithiocarbamate complex		
Ecology - soil	Adsorbs into the soil.	

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Disposal must be done according to official regulations.

Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

Additional information : Do not re-use empty containers.

European List of Waste (LoW, EC 2000/532) : 13 02 06* - synthetic engine, gear and lubricating oils

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

19/08/2025 (Revision date) IE - en 13/17

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID	
14.1. UN number or ID n	14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.2. UN proper shipping name					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.3. Transport hazard class(es)					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.4. Packing group					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.5. Environmental haz	ards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
No supplementary informatio	n available				

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

National regulations

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes		
Section	Changed item	Comments
	Revision date	Modified
	Supersedes	Modified
6.1	General measures	Added
9.1	Colour	Added
10.5	Incompatible materials	Added
13.1	European List of Waste (LoW, EC 2000/532)	Added

Abbreviations and acronyms:		
ACGIH	American Conference of Government Industrial Hygienists	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
CAS-No.	Chemical Abstract Service number	
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008	
COD	Chemical oxygen demand (COD)	
CSA	Chemical safety assessment	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	

19/08/2025 (Revision date) IE - en 15/17

Safety Data Sheet

Abbreviations and acronyms:		
EC-No.	European Community number	
EC50	Median effective concentration	
ED	Endocrine disruptor	
EN	European Standard	
EWC	European waste catalogue	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
Log Kow	Partition coefficient n-octanol/water (Log Kow)	
Log Pow	Partition coefficient n-octanol/water (Log Pow)	
MAK	maximum workplace concentration	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
N.O.S.	Not Otherwise Specified	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
OSHA	Occupational Safety Health Administration	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
PPE	Personal protection equipment	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
TF	Technical function	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
TWA	Time Weighted Average	
VOC	Volatile Organic Compounds	
vPvB	Very Persistent and Very Bioaccumulative	
UFI	Unique Formula Identifier	

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains C14-16-18 Alkyl phenol, Molybdenum polysulphide long chain alkyl dithiocarbamate complex. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.