



Motor Oil Synth SL 0W-30
Fully-Synthetic Passenger Car Motor Oil

Product Code: 79600

Motor Oil Synth SL 0W-30 is an universal very high performance engine oil based on fully synthetic base oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF).

Motor Oil Synth SL 0W-30 is formulated with high quality synthetic and PAO (Poly-alpha-olefin) base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

Motor Oil Synth SL 0W-30 meets the following performance criteria:

ACEA A3/B4	API SL	BMW LL-01
MB 229.5	Renault RN 0700/0710	Volvo 95200356
MB 226.5	VW 502.00/505.00	

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	0W-30
Density @15°C	kg/m ³	ASTM D4052	843.4
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	66.7
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	12.1
Viscosity Index		ASTM D2270	180
Viscosity CCS @-35°C	cP	ASTM D5293	5400
Flash Point COC	°C	ASTM D92	>210
Pour Point	°C	ASTM D7346	-51
Total Base Number	mgKOH/g	ASTM D2896	10.3

Date Issued: 4-12-2025	Supersedes: 22-9-2025	Revision Nr.: 05
------------------------	-----------------------	------------------