

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : 76790 - 4-Stroke Motorcycle Oil Synthetic 20W-50
Product code : 76790

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Intended for general public
Main use category : Industrial use, Professional use, Consumer use
Function or use category : Lubricants and additives

1.3. Details of the supplier of the safety data sheet

Transnational Blenders bv
Wieldrechtseweg 37
NL 3316 BG Dordrecht, Netherlands, Zuid Holland
Netherlands
T +31 (0)78 6527652
technical@tnb.nl, www.tnb.nl

1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains Molybdenum polysulphide long chain alkyl dithiocarbamate complex.
May produce an allergic reaction.
EUH210 - Safety data sheet available on request.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

76790 - 4-Stroke Motorcycle Oil Synthetic 20W-50

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil substance with a Community workplace exposure limit (Note L)	CAS-No.: 72623-87-1 EC-No.: 276-738-4 EC Index-No.: 649-483-00-5 REACH-no: 01-2119474889-13	≥ 45 – < 55	Asp. Tox. 1, H304
1-decene, homopolymer, hydrogenated (Polymer) substance with national workplace exposure limit(s) (BG)	CAS-No.: 68037-01-4 EC-No.: 500-183-1 REACH-no: 01-2119486452-34	≥ 25 – < 45	Not classified
Distillates (petroleum), hydrotreated heavy paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH, TR); substance with a Community workplace exposure limit (Note L)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25	≥ 0.1 – < 3	Not classified
Distillates (petroleum), solvent-dewaxed heavy paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH, TR); substance with a Community workplace exposure limit (Note L)	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6 REACH-no: 01-2119471299-27	≥ 0.1 – < 3	Asp. Tox. 1, H304
Zinc O,O',O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) substance with national workplace exposure limit(s) (SK)	CAS-No.: 2215-35-2 EC-No.: 218-679-9 REACH-no: 01-2119953275-34	≥ 0.3 – < 3	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (Note L)	CAS-No.: 64742-70-7 EC-No.: 265-174-4 EC Index-No.: 649-477-00-2 REACH-no: 01-2119487080-42	≥ 0.1 – < 3	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed light paraffinic substance with national workplace exposure limit(s) (BE, BG, CZ, DK, ES, FI, GR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SK, IS, NO, CH); substance with a Community workplace exposure limit (Note L)	CAS-No.: 64742-56-9 EC-No.: 265-159-2 EC Index-No.: 649-469-00-9 REACH-no: 01-2119480132-48	≥ 0.1 – < 3	Asp. Tox. 1, H304
Molybdenum polysulphide long chain alkyl dithiocarbamate complex substance with a Community workplace exposure limit	EC-No.: 457-320-2 REACH-no: 01-0000019337-66	< 0.3	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Chronic 3, H412

76790 - 4-Stroke Motorcycle Oil Synthetic 20W-50

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate)	CAS-No.: 2215-35-2 EC-No.: 218-679-9 REACH-no: 01-2119953275-34	(15 ≤ C < 20) Eye Irrit. 2; H319 (15 ≤ C < 20) Skin Irrit. 2; H315 (20 ≤ C < 100) Eye Dam. 1; H318

Note L: The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: None under normal conditions.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Precautionary measures fire	: Exercise caution when fighting any chemical fire.
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

76790 - 4-Stroke Motorcycle Oil Synthetic 20W-50

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid spilling the product, as this might cause falls. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with skin and eyes.
Handling temperature : ≤ 40 °C
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Provide local exhaust or general room ventilation.
Storage conditions : Keep cool. Protect from sunlight.
Storage temperature : ≤ 40 °C
Storage area : Store in a well-ventilated place. Store away from heat.
Special rules on packaging : Keep only in original container. Store in a closed container.
Packaging materials : Store always product in container of same material as original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

76790 - 4-Stroke Motorcycle Oil Synthetic 20W-50

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m ³
IOEL STEL	10 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA	5 ppm Form: inhalable fraction
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m ³
IOEL STEL	10 mg/m ³
Ireland - Occupational Exposure Limits	
OEL TWA	5 ppm Form: inhalable fraction
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m ³ ACGIH TLV (inhalable fraction)
Ireland - Occupational Exposure Limits	
OEL TWA	5 ppm Form: inhalable fraction
Molybdenum polysulphide long chain alkyl dithiocarbamate complex	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m ³
IOEL STEL	10 mg/m ³
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m ³
IOEL STEL	10 mg/m ³

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:

Gloves. Safety glasses. Protective clothing.

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Safety glasses

76790 - 4-Stroke Motorcycle Oil Synthetic 20W-50

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	≥ 0.35		EN ISO 374

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: brown.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: -33 °C (ASTM D7346)
Boiling point	: Not available
Flammability	: Non flammable.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 201 °C (ASTM D92)
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 142.5 mm²/s @ 40°C (ASTM D7042)
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 860 kg/m³ @ 15°C (ASTM D4052)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

No additional information available

76790 - 4-Stroke Motorcycle Oil Synthetic 20W-50

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 oral (rat)	> 5000 mg/kg 401 Acute Oral Toxicity Test
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (mg/l)	> mg/l
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5 mg/l/4h 403 Acute Inhalation Toxicity Test

Zinc O,O',O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)

LD50 oral (rat)	2230 mg/kg bodyweight OECD 401
LD50 dermal (rabbit)	> 25000 mg/kg bodyweight OECD 402
LC50 inhalation (rat) (mg/l)	> 2 mg/l OECD 403 (1 hour)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

LD50 oral (rat)	> 5000 (<) mg/kg 401 Acute Oral Toxicity Test
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5 mg/l/4h 403 Acute Inhalation Toxicity Test

Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)

LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 2000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	5 mg/l/4h

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

LD50 oral (rat)	> 5000 mg/kg 401 Acute Oral Toxicity Test
-----------------	---

76790 - 4-Stroke Motorcycle Oil Synthetic 20W-50

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test
Molybdenum polysulphide long chain alkyl dithiocarbamate complex	
LD50 oral (rat)	> 2000 mg/kg OECD Test Guideline 425
LD50 dermal (rat)	> 2000 mg/kg OECD Test Guideline 402
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)	
LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 2000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h
1-decene, homopolymer, hydrogenated (68037-01-4)	
LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rat)	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.2 mg/l/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)	
NOAEL (animal/male, F1)	160 mg/kg OECD 422
Molybdenum polysulphide long chain alkyl dithiocarbamate complex	
NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)	
NOAEL (oral, rat, 90 days)	160 mg/kg bodyweight
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Molybdenum polysulphide long chain alkyl dithiocarbamate complex	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight/day OECD Test Guideline 407

76790 - 4-Stroke Motorcycle Oil Synthetic 20W-50

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Molybdenum polysulphide long chain alkyl dithiocarbamate complex	
NOAEL (dermal, rat/rabbit, 90 days)	670 mg/kg bodyweight/day OECD Test Guideline 410
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day
1-decene,homopolymer,hydrogenated (68037-01-4)	
NOAEL (subacute, oral, animal/male, 28 days)	6245 mg/kg bodyweight
NOAEL (oral, rat, 90 days)	4159.4 mg/kg bodyweight/day
Aspiration hazard	: Not classified
76790 - 4-Stroke Motorcycle Oil Synthetic 20W-50	
Viscosity, kinematic	142.5 mm ² /s @ 40°C (ASTM D7042)
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Viscosity, kinematic	20.8 mm ² /s @ 40°C
Zinc O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)	
Viscosity, kinematic	270.4 mm ² /s @40°C
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
Viscosity, kinematic	150 (1.99 – 847) mm ² /s @40°C
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)	
Viscosity, kinematic	19 mm ² /s @40°C
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
Viscosity, kinematic	1.99 – 847 mm ² /s Temp.: '40°C
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)	
Viscosity, kinematic	47 mm ² /s
1-decene,homopolymer,hydrogenated (68037-01-4)	
Viscosity, kinematic	46000000 mm ² /s @40°C

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Zinc O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)	
LC50 - Fish [1]	46 mg/l Sheepshead Minnow
LC50 - Fish [2]	4.5 mg/l Oncorhynchus mykiss
EC50 - Crustacea [1]	23 mg/l Daphnia magna (OECD 202)

76790 - 4-Stroke Motorcycle Oil Synthetic 20W-50

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)	
EC50 72h - Algae [1]	24 mg/l Desmodesmus subspicatus
NOEC chronic fish	1.8 mg/l Rainbow Trout, 4 Days
NOEC chronic crustacea	0.4 mg/l Daphnia magna (21d)
NOEC chronic algae	10 mg/l Desmodesmus subspicatus (72h)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 1000 mg/l Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Pseudokirchneriella subcapitata (OECD 201)
NOEC chronic fish	> 1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)
NOEC chronic algae	100 mg/l Pseudokirchneriella subcapitata (72h)
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas (OECD 203)
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna (OECD 202)
NOEC chronic fish	≥ 1000 mg/l Oncorhynchus mykiss
NOEC chronic crustacea	> 10 mg/l Daphnia magna (21d) (OECD 211)
NOEC chronic algae	> 100 mg/l Pseudokirchneriella subcapitata (72h) (OECD 201)
Molybdenum polysulphide long chain alkyl dithiocarbamate complex	
LC50 - Fish [1]	> 94.8 mg/l Oncorhynchus mykiss (OECD 203)
LC50 - Fish [2]	> 670 mg/l Oncorhynchus mykiss (OECD 203)
EC50 - Crustacea [1]	50 mg/l Daphnia magna (OECD 202)
EC50 72h - Algae [1]	14 mg/l Pseudokirchneriella subcapitata (OECD 201)
NOEC (chronic)	100 mg/l
NOEC chronic fish	94.8 mg/l (Oncorhynchus mykiss (rainbow trout) OECD Test Guideline 203 (96h)
NOEC chronic crustacea	100 mg/l Daphnia magna (OECD 211) (21d)
NOEC chronic algae	4.05 mg/l
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 Daphnia magna
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)
NOEC chronic algae	100 mg/l Pseudokirchneriella subcapitata (72h)
1-decene,homopolymer,hydrogenated (68037-01-4)	
LC50 - Fish [1]	> 1000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l

76790 - 4-Stroke Motorcycle Oil Synthetic 20W-50

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.2. Persistence and degradability

76790 - 4-Stroke Motorcycle Oil Synthetic 20W-50

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Persistence and degradability	Readily biodegradable.
Biodegradation	< 60 % OECD TG 301 F (28d)

Zinc O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)

Persistence and degradability	Not readily biodegradable.
Biodegradation	1.5 % OECD TG 301 B (28d)

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

Persistence and degradability	Readily biodegradable.
Biodegradation	< 60 % OECD TG 301 F (28d)

Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

Persistence and degradability	Inherently biodegradable.
Biodegradation	31 % OECD TG 301 F (28d)

Molybdenum polysulphide long chain alkyl dithiocarbamate complex

Persistence and degradability	Rapidly degradable
Biodegradation	23 % OECD Test Guideline 301B (29d)

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)

Persistence and degradability	Rapidly degradable
Biodegradation	31 %

1-decene,homopolymer,hydrogenated (68037-01-4)

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

12.3. Bioaccumulative potential

Zinc O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)

Partition coefficient n-octanol/water (Log Kow)	2.21 @ 20°C
---	-------------

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

Bioconcentration factor (BCF REACH)	260
-------------------------------------	-----

Molybdenum polysulphide long chain alkyl dithiocarbamate complex

BCF - Fish [1]	0.05 mg/l @ 25°C (Cyprinus carpio)
Bioconcentration factor (BCF REACH)	88 OECD Test Guideline 305
Partition coefficient n-octanol/water (Log Pow)	5.1 @ 20°C

1-decene,homopolymer,hydrogenated (68037-01-4)

Partition coefficient n-octanol/water (Log Pow)	> 10
---	------

76790 - 4-Stroke Motorcycle Oil Synthetic 20W-50

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.4. Mobility in soil

Zinc O,O',O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate) (2215-35-2)

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

Molybdenum polysulphide long chain alkyl dithiocarbamate complex

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

1-decene, homopolymer, hydrogenated (68037-01-4)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	> 6.2
--	-------

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.
European List of Waste (LoW, EC 2000/532)	: 13 02 06* - synthetic engine, gear and lubricating oils
HP Code	: HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated for transport				
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated

76790 - 4-Stroke Motorcycle Oil Synthetic 20W-50

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

76790 - 4-Stroke Motorcycle Oil Synthetic 20W-50

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 16: Other information

Indication of changes

Section	Changed item	Comments
	Revision date	Modified
	Supersedes	Modified
3	Composition/information on ingredients	Modified
4.1	First-aid measures for first aider	Added
4.1	First-aid measures general	Added
4.2	Symptoms/effects after eye contact	Added
4.2	Symptoms/effects after ingestion	Added
4.2	Symptoms/effects after inhalation	Added
4.2	Symptoms/effects after skin contact	Added
5.2	Explosion hazard	Added
5.2	Fire hazard	Added
5.3	Firefighting instructions	Added
6.1	Emergency procedures	Added
6.1	General measures	Added
6.3	For containment	Added
7.1	Additional hazards when processed	Added
7.2	Packaging materials	Added
7.2	Storage conditions	Modified
9	Freezing point	Modified
9	Viscosity, kinematic	Modified
9	Density	Modified
13.1	Waste disposal recommendations	Added
13.1	Sewage disposal recommendations	Added
13.1	Regional waste regulation	Added
13.1	Additional information	Added

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number

76790 - 4-Stroke Motorcycle Oil Synthetic 20W-50

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains Molybdenum polysulphide long chain alkyl dithiocarbamate complex. May produce an allergic reaction.
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

76790 - 4-Stroke Motorcycle Oil Synthetic 20W-50

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:

H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1B	Skin sensitisation, category 1B

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.